

18-2 UNSHIELDED PLENUM

PART NO. FPLP182URR



www.commoditycables.com

Description

18 AWG solid bare copper Two Conductor, unshielded with Plenum jacket.

Features and Benefits

RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us. Footage marked descending.

Suitable Application

Power Limited Fire Alarm Signaling Cable Monitor/Detection **Audio Circuits Control Circuits**

Standards

NEC Articles: 725, 760, 800 22-16 AWG: CMP, CL2P, CL3P, FPLP

14-12 AWG: CL3P, FPLP

Applicable Standards

UL Type	FPLP, CL2P, CMP	
ROHS	Yes	
Compliant	163	

Electricals

Voltage Rating	150 Volts
Temperature Rating	-5°C to 75°C
Capacitance	23pF/ft

Print Legend

COMMODITY CABLES, INC. 18 AWG 2C FIRE ALARM CABLE (UL) TYPE FPLP/CL2P c(UL) us TYPE CMP E498766 A1001. Made in USA

Toll Free: (866) 945-5051 Local: (770) 945-5051 Fax: (770) 945-9582 www.commoditycables.com







Construction Details	
Total Number Conductors	2
AWG	18
Stranding	Solid
Conductor Material	Bare copper
Insulation Material	Low smoke copolymer
Insulation Thickness	.008"
Nominal Insulation Diameter	.056"
Color Code	Black, Red
Cabling Overall Lay	2 1/2" left hand lay (4.8 twist per foot)
Final Jacket Material	Low smoke copolymer
Nominal Thickness	.015"
Jacket Color	Red
Nominal Jacket Diameter	.143"
Weight	24 lb
Ripcord	Yes

Print (Surface Print)	
Inkjet	Yes
Sequential Foot Marks	Yes

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.